# TEST REPORT



**Applicant** : Mid Ocean Brands B.V.

**Address** : Unit 711-716, Tower A, 83 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong

(The following sample(s) was (were) submitted and identified by client as)

**Sample Name** : stepless dimming table lamp 1200mAh battery

**Model/Item No.** : MO2478

**Vendor Code** : 107978

**Test Period** : From Oct. 10, 2026 to Oct. 15, 2026

**Tests Conducted** : As requested by the applicant, for details refer to attached page(s).

**Executive Summary:**

| No. | TESTED SAMPLE | STANDARD / REQUIREMENT | CONCLUSION |
|---|---|---|---|
| 1 | Tested material(s) of submitted sample(s) | Photobiological Safety of Lamps and Lamp Systems - EN 62471:2008 | PASS |

Signed for and on behalf of
Compliance Control Institute (Guangzhou) Co., Ltd.

Approved by:
Pascal SHI/Technical Director

Compliance Control Institute (Guangzhou) Co., Ltd.
Room 701, Building 2, No.89, Majun Street, Nansha District, Guangzhou, Guangdong, China
Tel：+86-20-84900678 Fax：+86-20-84910993
Email：cs@ccilab.com.cn Website：www.ccilab.com.cn

This report is governed by, and incorporates by reference, the General Terms and Conditions of Testing which could be obtained / consulted by request to CCI or via the webpage of Conditions of Testing in the official website: www.ccilab.com.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report sets forth our findings solely respect to the client's request(s) and the test results are obtained just with the submitted sample identified herein. The test results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. This report can not be reproduced except in full, without prior written permission of CCI. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful, and any offenders may be prosecuted to the fullest extent of the law.

TESTS CONDUCTED:

1. Photobiological Safety of Lamps and Lamp Systems

As per European Standard EN 62471:2008 on Photobiological Safety of Lamps and Lamp Systems.

| EN 62471 | | | |
|---|---|---|---|
| Clause | Requirement — Test | Result | Verdict |
| **4** | **Exposure Limits** | | P |
| 4.1 | General | | P |
| | The exposure limits in this standard is not less than 0,01 ms and not more than any 8-hour period and should be used as guides in the control of exposure | | P |
| | Detailed spectral data of a light source are generally required only if the luminance of the source exceeds $10^4$ cd·m$^{-2}$ | see clause 4.3 | NA |
| 4.3 | Hazard exposure limits | | P |
| 4.3.1 | Actinic UV hazard exposure limit for the skin and eye | | P |
| | The exposure limit for effective radiant exposure is 30 J·m$^{-2}$ within any 8-hour period | | P |
| | To protect against injury of the eye or skin from ultraviolet radiation exposure produced by a broadband source, the effective integrated spectral irradiance , $E_S$, of the light source shall not exceed the levels defined by: | | P |
| | $E_s \cdot t = \sum_{200}^{400} \sum_{l} E_\lambda(\lambda,t) \cdot S_{UV}(\lambda) \cdot \Delta t \cdot \Delta\lambda \le 30$ J·m$^{-2}$ | | P |
| | The permissible time for exposure to ultraviolet radiation incident upon the unprotected eye or skin shall be computed by: | | P |
| | $t_{max} = \frac{30}{E_s}$ s | | P |
| 4.3.2 | Near-UV hazard exposure limit for eye | | P |
| | For the spectral region 315 nm to 400 nm (UV-A) the total radiant exposure to the eye shall not exceed 10000 J·m$^{-2}$ for exposure times less than 1000 s. For exposure times greater than 1000 s (approximately 16 minutes) the UV-A irradiance for the unprotected eye, $E_{UVA}$, shall not exceed 10 W·m$^{-2}$. | | P |
| | The permissible time for exposure to ultraviolet radiation incident upon the unprotected eye for time less than 1000 s, shall be computed by: | | P |
| | $t_{max} \le \frac{10000}{E_{UVA}}$ s | | P |




This report is governed by, and incorporates by reference, the General Terms and Conditions of Testing which could be obtained / consulted by request to CCI or via the webpage of Conditions of Testing in the official website: www.ccilab.com.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report sets forth our findings solely respect to the client's request(s) and the test results are obtained just with the submitted sample identified herein. The test results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. This report can not be reproduced except in full, without prior written permission of CCI. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful, and any offenders may be prosecuted to the fullest extent of the law.

| EN 62471 | | | |
|---|---|---|---|
| Clause | Requirement — Test | Result | Verdict |
| 4.3.3 | Retinal blue light hazard exposure limit | | P |
| | To protect against retinal photochemical injury from chronic blue-light exposure, the integrated spectral radiance of the light source weighted against the blue-light hazard function, B(λ), i.e., the blue-light weighted radiance , $L_B$, shall not exceed the levels defined by: | | P |
| | $L_B \cdot t = \sum_{300}^{700}\sum_{t} L_\lambda(\lambda,t)\cdot B(\lambda)\cdot \Delta t\cdot \Delta\lambda \le 10^6$ J·m$^{-2}$·sr$^{-1}$ | for t ≤ $10^4$ s $t_{max} = 10^6/L_B$ | P |
| | $L_B = \sum_{300}^{700} L_\lambda \cdot B(\lambda)\cdot \Delta\lambda \le 100$ W·m$^{-2}$·sr$^{-1}$ | for t > $10^4$ s | NA |
| 4.3.4 | Retinal blue light hazard exposure limit - small source | | NA |
| | Thus the spectral irradiance at the eye $E_\lambda$, weighted against the blue-light hazard function B(λ) shall not exceed the levels defined by: | See table 4.2 | NA |
| | $E_B \cdot t = \sum_{300}^{700}\sum_{t} E_\lambda(\lambda,t)\cdot B(\lambda)\cdot \Delta t\cdot \Delta\lambda \le 100$ J·m$^{-2}$ | for t ≤ 100 s | NA |
| | $E_B = \sum_{300}^{700} E_\lambda \cdot B(\lambda)\cdot \Delta\lambda \le 1$ W·m$^{-2}$ | for t ≤ 100 s | NA |
| 4.3.5 | Retinal thermal hazard exposure limit | | P |
| | To protect against retinal thermal injury, the integrated spectral radiance of the light source, $L_\lambda$, weighted by the burn hazard weighting function R(λ) (from Figure 4.2 and Table 4.2), i.e., the burn hazard weighted radiance, shall not exceed the levels defined by: | | P |
| | $L_R = \sum_{380}^{1400} L_\lambda \cdot R(\lambda)\cdot \Delta\lambda \le \frac{50000}{\alpha \cdot t^{0,25}}$ W·m$^{-2}$·sr$^{-1}$ | (10 μs ≤ t ≤ 10 s) | P |
| 4.3.6 | Retinal thermal hazard exposure limit – weak visual stimulus | | P |
| | For an infrared heat lamp or any near-infrared source where a weak visual stimulus is inadequate to activate the aversion response, the near infrared (780 nm to 1400 nm) radiance, $L_{IR}$, as viewed by the eye for exposure times greater than 10 s shall be limited to: | | P |
| | $L_{IR} = \sum_{780}^{1400} L_\lambda \cdot R(\lambda)\cdot \Delta\lambda \le \frac{6000}{\alpha}$ W·m$^{-2}$·sr$^{-1}$ | t > 10 s | P |




This report is governed by, and incorporates by reference, the General Terms and Conditions of Testing which could be obtained / consulted by request to CCI or via the webpage of Conditions of Testing in the official website: www.ccilab.com.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report sets forth our findings solely respect to the client's request(s) and the test results are obtained just with the submitted sample identified herein. The test results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. This report can not be reproduced except in full, without prior written permission of CCI. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful, and any offenders may be prosecuted to the fullest extent of the law.

| EN 62471 | | | |
|---|---|---|---|
| Clause | Requirement — Test | Result | Verdict |
| 4.3.7 | Infrared radiation hazard exposure limits for the eye | | P |
| | The avoid thermal injury of the cornea and possible delayed effects upon the lens of the eye (cataractogenesis), ocular exposure to infrared radiation, $E_{IR}$, over the wavelength range 780 nm to 3000 nm, for times less than 1000 s, shall not exceed: | | P |
| | $E_{IR} = \sum_{780}^{3000} E_\lambda \cdot \Delta\lambda \le 18000 \cdot t^{0,75}$ $W \cdot m^{-2}$ | t ≤ 1000 s | NA |
| | For times greater than 1000 s the limit becomes: | | P |
| | $E_{IR} = \sum_{780}^{3000} E_\lambda \cdot \Delta\lambda \le 100$ $W \cdot m^{-2}$ | t > 1000 s | P |
| 4.3.8 | Thermal hazard exposure limit for the skin | | P |
| | Visible and infrared radiant exposure (380 nm to 3000 nm) of the skin shall be limited to: | | P |
| | $E_H \cdot t = \sum_{380}^{3000} \sum_{t} E_\lambda(\lambda,t) \cdot \Delta t \cdot \Delta\lambda \le 20000 \cdot t^{0,25}$ $J \cdot m^{-2}$ | | P |

| | | | |
|---|---|---|---|
| 5 | **MEASUREMENT OF LAMPS AND LAMP SYSTEMS** | | P |
| 5.1 | Measurement conditions | | P |
| | Measurement conditions shall be reported as part of the evaluation against the exposure limits and the assignment of risk classification. | | P |
| 5.1.1 | Lamp ageing (seasoning) | | NA |
| | Seasoning of lamps shall be done as stated in the appropriate IEC lamp standard. | | NA |
| 5.1.2 | Test environment | | P |
| | For specific test conditions, see the appropriate IEC lamp standard or in absence of such standards, the appropriate national standards or manufacturer's recommendations. | | P |
| 5.1.3 | Extraneous radiation | | P |
| | Careful checks should be made to ensure that extraneous sources of radiation and reflections do not add significantly to the measurement results. | | P |
| 5.1.4 | Lamp operation | | NA |




This report is governed by, and incorporates by reference, the General Terms and Conditions of Testing which could be obtained / consulted by request to CCI or via the webpage of Conditions of Testing in the official website: www.ccilab.com.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report sets forth our findings solely respect to the client's request(s) and the test results are obtained just with the submitted sample identified herein. The test results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. This report can not be reproduced except in full, without prior written permission of CCI. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful, and any offenders may be prosecuted to the fullest extent of the law.

| EN 62471 | | | |
|---|---|---|---|
| Clause | Requirement — Test | Result | Verdict |
| | Operation of the test lamp shall be provided in accordance with: | | NA |
| | the appropriate EN lamp standard, or | | NA |
| | the manufacturer' s recommendation | | NA |
| 5.1.5 | Lamp system operation | | P |
| | The power source for operation of the test lamp shall be provided in accordance with: | | P |
| | the appropriate EN standard, or the manufacturer' s recommendation | | NA |
| | the manufacturer' s recommendation | | P |
| 5.2 | Measurement procedure | | P |
| 5.2.1 | Irradiance measurements | | P |
| | Minimum aperture diameter 7mm. | | P |
| | Maximum aperture diameter 50 mm. | | P |
| | The measurement shall be made in that position of the beam giving the maximum reading. | | P |
| | The measurement instrument is adequate calibrated. | | P |
| 5.2.2 | Radiance measurements | | P |
| 5.2.2.1 | Standard method | | NA |
| | The measurements made with an optical system. | | NA |
| | The instrument shall be calibrated to read in absolute radiant power per unit receiving area and per unit solid angle to acceptance averaged over the field of view of the instrument. | | NA |
| 5.2.2.2 | Alternative method | | NA |
| | Alternatively to an imaging radiance set-up, an irradiance measurement set-up with a circular field stop placed at the source can be used to perform radiance measurements. | | NA |
| 5.2.3 | Measurement of source size | | P |
| | The determination of α, the angle subtended by a source, requires the determination of the 50% emission points of the source. | | P |
| 5.2.4 | Pulse width measurement for pulsed sources | | NA |
| | The determination of Δt, the nominal pulse duration of a source, requires the determination of the time during which the emission is > 50% of its peak value. | | NA |




This report is governed by, and incorporates by reference, the General Terms and Conditions of Testing which could be obtained / consulted by request to CCI or via the webpage of Conditions of Testing in the official website: www.ccilab.com.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report sets forth our findings solely respect to the client's request(s) and the test results are obtained just with the submitted sample identified herein. The test results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. This report can not be reproduced except in full, without prior written permission of CCI. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful, and any offenders may be prosecuted to the fullest extent of the law.

| EN 62471 | | | |
|---|---|---|---|
| Clause | Requirement — Test | Result | Verdict |
| 5.3 | Analysis methods | | P |
| 5.3.1 | Weighting curve interpolations | | P |
| | To standardize interpolated values, use linear interpolation on the log of given values to obtain intermediate points at the wavelength intervals desired. | see table 4.1 | P |
| 5.3.2 | Calculations | | P |
| | The calculation of source hazard values shall be performed by weighting the spectral scan by the appropriate function and calculating the total weighted energy. | | P |
| 5.3.3 | Measurement uncertainty | | P |
| | The quality of all measurement results must be quantified by an analysis of the uncertainty. | see Annex C in the norm | P |

| | | | |
|---|---|---|---|
| 6 | **LAMP CLASSIFICATION** | | P |
| | For the purposes of this standard it was decided that the values shall be reported as follows: | see table 6.1 | P |
| | for lamps intended for general lighting service, the hazard values shall be reported as either irradiance or radiance values at a distance which produces an illuminance of 500 lux, but not at a distance less than 200 mm | | P |
| | for all other light sources, including pulsed lamp sources, the hazard values shall be reported at a distance of 200 mm | | NA |
| 6.1 | Continuous wave lamps | | P |
| 6.1.1 | Except Group | | P |
| | In the except group are lamps, which does not pose any photobiological hazard. The requirement is met by any lamp that does not pose: | | P |
| | – an actinic ultraviolet hazard ($E_S$) within 8-hours exposure (30000 s), nor | | P |
| | – a near-UV hazard ($E_{UVA}$) within 1000 s, (about 16 min), nor | | P |
| | – a retinal blue-light hazard ($L_B$) within 10000 s (about 2,8 h), nor | | P |
| | – a retinal thermal hazard ($L_R$) within 10 s, nor | | P |
| | – an infrared radiation hazard for the eye ($E_{IR}$) within 1000 s | | P |



This report is governed by, and incorporates by reference, the General Terms and Conditions of Testing which could be obtained / consulted by request to CCI or via the webpage of Conditions of Testing in the official website: www.ccilab.com.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report sets forth our findings solely respect to the client's request(s) and the test results are obtained just with the submitted sample identified herein. The test results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. This report can not be reproduced except in full, without prior written permission of CCI. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful, and any offenders may be prosecuted to the fullest extent of the law.

| EN 62471 | | | |
|---|---|---|---|
| Clause | Requirement — Test | Result | Verdict |
| 6.1.2 | Risk Group 1 (Low-Risk) | | NA |
| | In this group are lamps, which exceeds the limits for the except group but that does not pose: | | NA |
| | – an actinic ultraviolet hazard ($E_S$) within 10000 s, nor | | NA |
| | – a near ultraviolet hazard ($E_{UVA}$) within 300 s, nor | | NA |
| | – a retinal blue-light hazard ($L_B$) within 100 s, nor | | NA |
| | – a retinal thermal hazard ($L_R$) within 10 s, nor | | NA |
| | – an infrared radiation hazard for the eye ($E_{IR}$) within 100 s | | NA |
| | Lamps that emit infrared radiation without a strong visual stimulus and do not pose a near-infrared retinal hazard ($L_{IR}$), within 100 s are in Risk Group 1. | | NA |
| 6.1.3 | Risk Group 2 (Moderate-Risk) | | NA |
| | This requirement is met by any lamp that exceeds the limits for Risk Group 1, but that does not pose: | | NA |
| | – an actinic ultraviolet hazard ($E_S$) within 1000 s exposure, nor | | NA |
| | – a near ultraviolet hazard ($E_{UVA}$) within 100 s, nor | | NA |
| | – a retinal blue-light hazard ($L_B$) within 0,25 s (aversion response), nor | | NA |
| | – a retinal thermal hazard ($L_R$) within 0,25 s (aversion response), nor | | NA |
| | – an infrared radiation hazard for the eye ($E_{IR}$) within 10 s | | NA |
| | Lamps that emit infrared radiation without a strong visual stimulus and do not pose a near-infrared retinal hazard ($L_{IR}$), within 10 s are in Risk Group 2. | | NA |
| 6.1.4 | Risk Group 3 (High-Risk) | | NA |
| | Lamps which exceed the limits for Risk Group 2 are in Group 3. | | NA |




This report is governed by, and incorporates by reference, the General Terms and Conditions of Testing which could be obtained / consulted by request to CCI or via the webpage of Conditions of Testing in the official website: www.ccilab.com.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report sets forth our findings solely respect to the client's request(s) and the test results are obtained just with the submitted sample identified herein. The test results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. This report can not be reproduced except in full, without prior written permission of CCI. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful, and any offenders may be prosecuted to the fullest extent of the law.

| EN 62471 | | | |
|---|---|---|---|
| Clause | Requirement — Test | Result | Verdict |
| 6.2 | Pulsed lamps | | NA |
| | Pulse lamp criteria shall apply to a single pulse and to any group of pulses within 0,25s. | | NA |
| | A pulsed lamp shall be evaluated at the highest nominal energy loading as specified by the manufacturer. | | NA |
| | The risk group determination of the lamp being tested shall be made as follows: | | NA |
| | – a lamp that exceeds the exposure limit shall be classified as belonging to Risk Group 3 (High-Risk) | | NA |
| | – for single pulsed lamps, a lamp whose weighted radiant exposure or weighted radiance does is below the EL shall be classified as belonging to the Exempt Group | | NA |
| | – for repetitively pulsed lamps, a lamp whose weighted radiant exposure or weighted radiance dose is below the EL, shall be evaluated using the continuous wave risk criteria discussed in clause 6.1, using time averaged values of the pulsed emission | | NA |




This report is governed by, and incorporates by reference, the General Terms and Conditions of Testing which could be obtained / consulted by request to CCI or via the webpage of Conditions of Testing in the official website: www.ccilab.com.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report sets forth our findings solely respect to the client's request(s) and the test results are obtained just with the submitted sample identified herein. The test results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. This report can not be reproduced except in full, without prior written permission of CCI. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful, and any offenders may be prosecuted to the fullest extent of the law.

| EN 62471 | | | |
|---|---|---|---|
| Clause | Requirement — Test | Result | Verdict |

| **Table 4.1** | Spectral weighting function for assessing ultraviolet hazards for skin and eye | | P |
|---|---|---|---|
| **Wavelength[1] λ, nm** | **UV hazard function $S_{uv}(\lambda)$** | **Wavelength λ, nm** | **UV hazard function $S_{uv}(\lambda)$** |
| 200 | 0,030 | 313* | 0,006 |
| 205 | 0,051 | 315 | 0,003 |
| 210 | 0,075 | 316 | 0,0024 |
| 215 | 0,095 | 317 | 0,0020 |
| 220 | 0,120 | 318 | 0,0016 |
| 225 | 0,150 | 319 | 0,0012 |
| 230 | 0,190 | 320 | 0,0010 |
| 235 | 0,240 | 322 | 0,00067 |
| 240 | 0,300 | 323 | 0,00054 |
| 245 | 0,360 | 325 | 0,00050 |
| 250 | 0,430 | 328 | 0,00044 |
| 254* | 0,500 | 330 | 0,00041 |
| 255 | 0,520 | 333* | 0,00037 |
| 260 | 0,650 | 335 | 0,00034 |
| 265 | 0,810 | 340 | 0,00028 |
| 270 | 1,000 | 345 | 0,00024 |
| 275 | 0,960 | 350 | 0,00020 |
| 280* | 0,880 | 355 | 0,00016 |
| 285 | 0,770 | 360 | 0,00013 |
| 290 | 0,640 | 365* | 0,00011 |
| 295 | 0,540 | 370 | 0,000093 |
| 297* | 0,460 | 375 | 0,000077 |
| 300 | 0,300 | 380 | 0,000064 |
| 303* | 0,120 | 385 | 0,000053 |
| 305 | 0,060 | 390 | 0,000044 |
| 308 | 0,026 | 395 | 0,000036 |
| 310 | 0,015 | 400 | 0,000030 |

[1] Wavelengths chosen are representative: other values should be obtained by logarithmic interpolation at intermediate wavelengths.

* Emission lines of a mercury discharge spectrum.




This report is governed by, and incorporates by reference, the General Terms and Conditions of Testing which could be obtained / consulted by request to CCI or via the webpage of Conditions of Testing in the official website: www.ccilab.com.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report sets forth our findings solely respect to the client's request(s) and the test results are obtained just with the submitted sample identified herein. The test results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. This report can not be reproduced except in full, without prior written permission of CCI. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful, and any offenders may be prosecuted to the fullest extent of the law.

| EN 62471 | | | |
|---|---|---|---|
| Clause | Requirement — Test | Result | Verdict |

| **Table 4.2** | Spectral weighting functions for assessing retinal hazards from broadband optical sources | NA |
|---|---|---|

| **Wavelength nm** | **Blue-light hazard function B (λ)** | **Burn hazard function R (λ)** |
|---|---|---|
| 300 | 0,01 | |
| 305 | 0,01 | |
| 310 | 0,01 | |
| 315 | 0,01 | |
| 320 | 0,01 | |
| 325 | 0,01 | |
| 330 | 0,01 | |
| 335 | 0,01 | |
| 340 | 0,01 | |
| 345 | 0,01 | |
| 350 | 0,01 | |
| 355 | 0,01 | |
| 360 | 0,01 | |
| 365 | 0,01 | |
| 370 | 0,01 | |
| 375 | 0,01 | |
| 380 | 0,01 | 0,1 |
| 385 | 0,013 | 0,13 |
| 390 | 0,025 | 0,25 |
| 395 | 0,05 | 0,5 |
| 400 | 0,10 | 1,0 |
| 405 | 0,20 | 2,0 |
| 410 | 0,40 | 4,0 |
| 415 | 0,80 | 8,0 |
| 420 | 0,90 | 9,0 |
| 425 | 0,95 | 9,5 |
| 430 | 0,98 | 9,8 |
| 435 | 1,00 | 10,0 |
| 440 | 1,00 | 10,0 |
| 445 | 0,97 | 9,7 |
| 450 | 0,94 | 9,4 |
| 455 | 0,90 | 9,0 |
| 460 | 0,80 | 8,0 |
| 465 | 0,70 | 7,0 |
| 470 | 0,62 | 6,2 |
| 475 | 0,55 | 5,5 |
| 480 | 0,45 | 4,5 |
| 485 | 0,40 | 4,0 |
| 490 | 0,22 | 2,2 |


Compliance Control Institute (Guangzhou) Co., Ltd.
Room 701, Building 2, No.89, Majun Street, Nansha District, Guangzhou, Guangdong, China
Tel：+86-20-84900678 Fax：+86-20-84910993
Email：cs@ccilab.com.cn Website：www.ccilab.com.cn



This report is governed by, and incorporates by reference, the General Terms and Conditions of Testing which could be obtained / consulted by request to CCI or via the webpage of Conditions of Testing in the official website: www.ccilab.com.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report sets forth our findings solely respect to the client's request(s) and the test results are obtained just with the submitted sample identified herein. The test results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. This report can not be reproduced except in full, without prior written permission of CCI. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful, and any offenders may be prosecuted to the fullest extent of the law.

| | | |
|---|---|---|
| 495 | 0,16 | 1,6 |
| 500-600 | $10^{[(450-\lambda)/50]}$ | 1,0 |
| 600-700 | 0,001 | 1,0 |
| 700-1050 | | $10^{[(700-\lambda)/500]}$ |
| 1050-1150 | | 0,2 |
| 1150-1200 | | $0.2 \cdot 10^{0,02(1150-\lambda)}$ |
| 1200-1400 | | 0,02 |

| EN 62471 | | | |
|---|---|---|---|
| Clause | Requirement — Test | Result | Verdict |

| **Table 5.4** | Summary of the ELs for the surface of the skin or cornea (irradiance based values) | | | | P |
|---|---|---|---|---|---|
| **Hazard Name** | **Relevant equation** | **Wavelength range nm** | **Exposure duration sec** | **Limiting aperture rad (deg)** | **EL in terms of constant irradiance W•m$^{-2}$** |
| Actinic UV skin & eye | $E_S = \sum E_\lambda \cdot S(\lambda) \cdot \Delta\lambda$ | 200 – 400 | < 30000 | 1,4 (80) | 30/t |
| Eye UV-A | $E_{UVA} = \sum E_\lambda \cdot \Delta\lambda$ | 315 – 400 | ≤1000<br>>1000 | 1,4 (80) | 10000/t<br>10 |
| Blue-light small source | $E_B = \sum E_\lambda \cdot B(\lambda) \cdot \Delta\lambda$ | 300 – 700 | ≤100<br>>100 | < 0,011 | 100/t<br>1,0 |
| Eye IR | $E_{IR} = \sum E_\lambda \cdot \Delta\lambda$ | 780 –3000 | ≤1000<br>>1000 | 1,4 (80) | 18000/t $^{0,75}$<br>100 |
| Skin thermal | $E_H = \sum E_\lambda \cdot \Delta\lambda$ | 380 – 3000 | < 10 | 2π sr | 20000/t $^{0,75}$ |

| **Table 5.5** | Summary of the ELs for the retina (radiance based values) | | | | P |
|---|---|---|---|---|---|
| **Hazard Name** | **Relevant equation** | **Wavelength range nm** | **Exposure duration sec** | **Field of view radians** | **EL in terms of constant radiance W•m$^{-2}$•sr$^{-1}$)** |
| Blue light | $L_B = \sum L_\lambda \cdot B(\lambda) \cdot \Delta\lambda$ | 300 – 700 | 0,25 – 10<br>10-100<br>100-10000<br>≥ 10000 | 0,011•√(t/10)<br>0,011<br>0,0011•√t<br>0,1 | $10^6$/t<br>$10^6$/t<br>$10^6$/t<br>100 |
| Retinal thermal | $L_R = \sum L_\lambda \cdot R(\lambda) \cdot \Delta\lambda$ | 380 – 1400 | < 0,25<br>0,25 – 10 | 0,0017<br>0,011•√(t/10) | 50000/(α•t$^{0,25}$)<br>50000/(α•t$^{0,25}$) |
| Retinal thermal (weak visual stimulus) | $L_{IR} = \sum L_\lambda \cdot R(\lambda) \cdot \Delta\lambda$ | 780 – 1400 | > 10 | 0,011 | 6000/α |




This report is governed by, and incorporates by reference, the General Terms and Conditions of Testing which could be obtained / consulted by request to CCI or via the webpage of Conditions of Testing in the official website: www.ccilab.com.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report sets forth our findings solely respect to the client's request(s) and the test results are obtained just with the submitted sample identified herein. The test results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. This report can not be reproduced except in full, without prior written permission of CCI. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful, and any offenders may be prosecuted to the fullest extent of the law.

| EN 62471 | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Clause | Requirement — Test | | | Result | | | | Verdict | |
| **Table 6.1**[1)] | Emission limits for risk groups of continuous wave lamps(High color temperature) | | | | | | | P | |
| **Risk** | **Action spectrum** | **Symbol** | **Units** | **Emission Measurement** | | | | | |
| | | | | **Exempt** | | **Low risk** | | **Mod risk** | |
| | | | | **Limit** | **Result** | **Limit** | **Result** | **Limit** | **Result** |
| Actinic UV | SUV(λ) | Es | W•m-2 | 0.001 | 1.18e-05 | 0,003 | - | 0,03 | - |
| Near UV | | EUVA | W•m-2 | 10 | 1.62e-03 | 33 | - | 100 | - |
| Blue light | B(λ) | LB | W•m-2•sr-1 | 100 | 2.27e+00 | 0000 | - | 4000000 | - |
| Blue light, small source | B(λ) | EB | W•m-2 | 1.0* | - | 1,0 | - | 400 | - |
| Retinal thermal | R(λ) | LR | W•m-2•sr-1 | 28000/α | 3.49e+00 | 28000/α | - | 71000/α | - |
| Retinal thermal, weak visual stimulus** | R(λ) | LIR | W•m-2•sr-1 | 6000/α | 2.00e+00 | 6000/α | - | 6000/α | - |
| IR radiation, eye | | EIR | W•m-2 | 100 | 1.68e-02 | 570 | - | 3200 | - |

* Small source defined as one with α < 0,011 radian. Averaging field of view at 10000 s is 0,1 radian.

** Involves evaluation of non-GLS source




This report is governed by, and incorporates by reference, the General Terms and Conditions of Testing which could be obtained / consulted by request to CCI or via the webpage of Conditions of Testing in the official website: www.ccilab.com.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report sets forth our findings solely respect to the client's request(s) and the test results are obtained just with the submitted sample identified herein. The test results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. This report can not be reproduced except in full, without prior written permission of CCI. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful, and any offenders may be prosecuted to the fullest extent of the law.

| EN 62471 | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Clause | Requirement — Test | | | Result | | | | Verdict | |
| **Table 6.1**[2)] | Emission limits for risk groups of continuous wave lamps(Low color temperature) | | | | | | | P | |
| **Risk** | **Action spectrum** | **Symbol** | **Units** | **Emission Measurement** | | | | | |
| | | | | **Exempt** | | **Low risk** | | **Mod risk** | |
| | | | | **Limit** | **Result** | **Limit** | **Result** | **Limit** | **Result** |
| Actinic UV | SUV(λ) | Es | W•m-2 | 0.001 | 3.48e-08 | 0,003 | - | 0,03 | - |
| Near UV | | EUVA | W•m-2 | 10 | 1.62e-04 | 33 | - | 100 | - |
| Blue light | B(λ) | LB | W•m-2•sr-1 | 100 | 2.27e-02 | 0000 | - | 4000000 | - |
| Blue light, small source | B(λ) | EB | W•m-2 | 1.0* | - | 1,0 | - | 400 | - |
| Retinal thermal | R(λ) | LR | W•m-2•sr-1 | 28000/α | 3.86e+00 | 28000/α | - | 71000/α | - |
| Retinal thermal, weak visual stimulus** | R(λ) | LIR | W•m-2•sr-1 | 6000/α | 2.06e-02 | 6000/α | - | 6000/α | - |
| IR radiation, eye | | EIR | W•m-2 | 100 | 6.54e-03 | 570 | - | 3200 | - |

* Small source defined as one with α < 0,011 radian. Averaging field of view at 10000 s is 0,1 radian.

** Involves evaluation of non-GLS source




This report is governed by, and incorporates by reference, the General Terms and Conditions of Testing which could be obtained / consulted by request to CCI or via the webpage of Conditions of Testing in the official website: www.ccilab.com.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report sets forth our findings solely respect to the client's request(s) and the test results are obtained just with the submitted sample identified herein. The test results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. This report can not be reproduced except in full, without prior written permission of CCI. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful, and any offenders may be prosecuted to the fullest extent of the law.

| EN 62471B ATTACHMENT | | | |
|---|---|---|---|
| Clause | Requirement — Test | Result | Verdict |

| | | | |
|---|---|---|---|
| | **CENELEC COMMON MODIFICATIONS (EN)** | | P |
| 4 | EXPOSURE LIMITS | | P |
| | Contents of the whole Clause 4 of IEC 62471:2006 moved into a new informative Annex ZB | | --- |
| | Clause 4 replaced by the following: | | P |
| | Limits of the Artificial Optical Radiation Directive (2006/25/EC) have been applied instead of those fixed in IEC 62471:2006 | | P |
| 4.1 | General | | P |
| | First paragraph deleted | | --- |

Table 6.1 — Emission limits for risk groups of continuous wave lamps (based on EU Directive 2006/25/EC) — P

| Risk | Action spectrum | Symbol | Units | Emission Measurement | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | | | | Exempt | | Low risk | | Mod risk | |
| | | | | Limit | Result | Limit | Result | Limit | Result |
| Actinic UV | $S_{UV}(\lambda)$ | Es | $W \cdot m^{-2}$ | 0.001 | 1.18e-05 | 0.003 | - | - | - |
| Near UV | | $E_{UVA}$ | $W \cdot m^{-2}$ | 0.33 | 1.62e-03 | 33 | - | - | - |
| Blue light | $B(\lambda)$ | $L_B$ | $W \cdot m^{-2} \cdot sr^{-1}$ | 100 | 2.27e+00 | 10000 | - | - | - |
| Blue light, small source | $B(\lambda)$ | $E_B$ | $W \cdot m^{-2}$ | 0.01* | - | 1,0 | - | - | - |
| Retinal thermal | $R(\lambda)$ | $L_R$ | $W \cdot m^{-2} \cdot sr^{-1}$ | 28000/α | 3.49e+00 | 28000/α | - | - | - |
| Retinal thermal, weak visual stimulus** | $R(\lambda)$ | $L_{IR}$ | $W \cdot m^{-2} \cdot sr^{-1}$ | 545000 0,0017≤ α ≤ 0,011 | 2.00e+00 | - | | | |
| | | | | 6000/α = 0,011≤ α ≤ 0,1 | - | | | | |
| IR radiation, eye | | $E_{IR}$ | $W \cdot m^{-2}$ | 100 | 1.68e-02 | 570 | - | 3200 | -- |

* Small source defined as one with α < 0,011 radian. Averaging field of view at 10000 s is 0,1 radian.

** Involves evaluation of non-GLS source




This report is governed by, and incorporates by reference, the General Terms and Conditions of Testing which could be obtained / consulted by request to CCI or via the webpage of Conditions of Testing in the official website: www.ccilab.com.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report sets forth our findings solely respect to the client's request(s) and the test results are obtained just with the submitted sample identified herein. The test results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. This report can not be reproduced except in full, without prior written permission of CCI. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful, and any offenders may be prosecuted to the fullest extent of the law.

# TEST REPORT



Photo Appendix






★★★★★End of Report★★★★★

Compliance Control Institute (Guangzhou) Co., Ltd.
Room 701, Building 2, No.89, Majun Street, Nansha District, Guangzhou, Guangdong, China
Tel：+86-20-84900678 Fax：+86-20-84910993
Email：cs@ccilab.com.cn Website：www.ccilab.com.cn

This report is governed by, and incorporates by reference, the General Terms and Conditions of Testing which could be obtained / consulted by request to CCI or via the webpage of Conditions of Testing in the official website: www.ccilab.com.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report sets forth our findings solely respect to the client's request(s) and the test results are obtained just with the submitted sample identified herein. The test results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. This report can not be reproduced except in full, without prior written permission of CCI. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful, and any offenders may be prosecuted to the fullest extent of the law.